

# Dual Window Water Vending Unit

CHOOSE FROM  
THE **LEADER!**

**NEW DESIGN  
& FEATURES!**



## FEATURES

- 8 selection buttons
- LED lighting (*energy efficient*)
- Pause/restart button
- MDB coin mechanism w/DEX
- Post carbon filter
- U.V. temperature flush
- 5 GPM U.V. light
- GFCI Power Cord
- Springless door design (*self closing*)
- Integral mounting flange
- Secure Design

## OPTIONS

- Remote monitoring
- Credit card acceptance
- Alkaline Water Filter

## LOCATIONS/APPLICATIONS

- Water Stores
- Car Washes
- Kiosks
- Retail Stores



## SPECIFICATIONS

### DIMENSIONS (Main Cabinet)

Height (Flange) ..... 37 inches  
Depth ..... 20 inches  
Width (Flange)..... 47 inches

### WEIGHT

Dry Shipping..... 304 lbs  
(Painted Unit)

### CAPACITY

Dispensing Flow ...5 GPM Max  
each dispenser

### FEED PRESSURE

Min..... 20 psi  
Max..... 100 psi

### PLUMBING CONNECTIONS

Feed..... 1/2 inch FNPT x 2  
(Unit has separate feed connections for each dispenser housing)

Drain ..... 1 inch FNPT x 2  
(Unit has separate drain connections for each dispenser housing) (1" I.D. Min. Hose)

### ELECTRICAL

3 amp, 110 VAC Grounded 60 HZ  
GFCI Circuit

# Coster

ENGINEERING

**A Division of Hiniker Company**

P.O. Box 3407 • Mankato, MN 56002

Telephone: 1-507-625-6621 • FAX: 1-507-625-9124

[www.costereng.com](http://www.costereng.com)

NAMA  
LISTED.



We reserve the right to amend these specifications at any time without notice. The only warranty applicable is the standard written Coster Engineering limited warranty. We make no other warranty, expressed or implied. Consult factory for details.