

Window Water

CHOOSE FROM
THE **LEADER!**

Vending Unit

**NEW DESIGN
& FEATURES!**



FEATURES

- 4 selection buttons
- LED lighting (energy efficient)
- Pause/restart button
- MDB coin mechanism w/DEX
- Post carbon filter
- U.V. temperature flush
- 5 GPM U.V. light
- GFCI Power Cord
- Springless door design (self closing)
- Integral mounting flange
- Secure Design

OPTIONS

- Remote monitoring
- Credit card acceptance
- Alkaline Water Filter

SPECIFICATIONS

DIMENSIONS

Height 35 inches
Depth 20 inches
Width 28 inches

FEED PRESSURE

Min..... 20 psi
Max..... 100 psi

W/FRONT FLANGE

Height 37 inches
Width 29 inches

PLUMBING

CONNECTIONS
Feed..... 1/2 inch FNPT
Drain 1 inch FNPT
(1" I.D. Min. Hose)

WEIGHT

Dry Shipping... 200 lbs

CAPACITY

Dispensing
Flow 5 GPM Max.

ELECTRICAL

2 1/2 amp, 110 VAC
Grounded 60 HZ
GFCI Circuit

LOCATIONS/APPLICATIONS

- Water Stores
- Car Washes
- Kiosks
- Retail Stores



Coster

ENGINEERING

A Division of Hiniker Company

P.O. Box 3407 • Mankato, MN 56002

Telephone: 1-507-625-6621 • FAX: 1-507-625-9124

www.costereng.com

**NAMA
LISTED.**



We reserve the right to amend these specifications at any time without notice. The only warranty applicable is the standard written Coster Engineering limited warranty. We make no other warranty, expressed or implied. Consult factory for details.