



COMMERCIAL WALL MOUNT ECONOMY REVERSE OSMOSIS SYSTEM CHOOSE FROM THE LEADER

Special Features:

- RO Elements: Extra Low Energy Thin Film
- Pressure Vessels: 304 Stainless Steel (SS)
- Frame: 409 SS
- Pump: Vane type
- Pump Pressure Gauge (liquid filled)
- Low Pressure Cutoff Switch
- Pre Filter: 1 Micron Sediment
- Inlet Filter Gauge
- Inlet Feed Electric Solenoid Valve
- Inlet Manual Shutoff Valve
- Product Reverse Flow Check Valve
- Waste Recycle Valve



Standard Features:

- Quality equipment manufactured with over 30 years of experience
- All-new look, traditional dependability
- Competitively priced units

Options:

- Product Total Dissolved Solids (TDS) Meter
- Float Shutoff Kit



COMMERCIAL REVERSE OSMOSIS UNIT CHOOSE FROM THE LEADER



Shown with cover.

Coster water machines provide top quality water and a top quality compliment to any store. With over 30 years in the business, Coster machines have a proven track record of dependability and success in the marketplace.

Dimensions:

- Height: 50 inches
- Depth: 7 inches
- Width: 24 inches

Specifications:

Elements	Production*	Recovery	Motor**	Weight (Approx.)	Inlet***	Outlets
Qty. 1 (4")	1,500 GPD	50%	1/2 HP	120 Lbs.	1/2" FNPT	3/8" JG

* Approximate product flow based on properly pretreated feed water of 1000 ppm TDS (as NaCl), 15° C (59° F) and silt density index less than 3. Production capacity may vary due to feed water temperature, pressure, quality and product back pressure.

** Electrical: Standard 120 VAC 60 HZ Single Phase

*** Inlet Pressure: 20 PSI Minimum (when running), 80 PSI Maximum.

A Division of Hiniker Company
58766 240th St. • Mankato, MN 56001
Telephone: 1-507-625-6621 • FAX: 1-507-625-9124
www.costereng.com



We reserve the right to amend these specifications at any time without notice. The only warranty applicable is the standard written Coster Engineering limited warranty. We make no other warranty, expressed or implied. Consult factory for details.