



DUAL WATER DISPENSING SYSTEM 1840

CHOOSE FROM THE LEADER

Special Features:

- Dual Dispenser
- Accommodates 1 through 5 gallon containers, including 5 gallon insulated containers.
- Automatic shut off on occurrence of an internal leak. (Charging and vending)
- Shut down when the feed pressure drops too low. (Pressure pump unit only)
- Preset starting volumes, 1 & 5 gallons. (All volumes field adjustable) with stop button.
- Automatic shut off when the ultraviolet lamp fails.
- Removable drain tank for ease of service.
- Adjustable legs.
- Small cabinet size.
- Ease of component access and repair.



Standard Features:

- Quality equipment manufactured with over 30 years of experience
- Two Vending Stations In One
- Accommodates Peak Traffic Periods
- Attractive, Space-Efficient Design
- Polished Stainless Steel Front
- 60-gallon Storage Capacity

Options:

- Auxiliary water port—Mister System.
- Auxiliary water meter.



DUAL WATER DISPENSING SYSTEM 1840 CHOOSE FROM THE LEADER

Capacity (1840 Pressure Pump Units)

- Element: 4 x 40
- Operating Pressure: 120 PSI
- Product Flow: 1 GPM*
- Product Flow: 1440 GPD*
- Concentrate Flow: 1 GPM
- % Recovery (Nominal): 50

* Approximate initial product flow based on properly pretreated feed water of 1000 ppm TDS (As NaCl), 20° C (68° F) and silt density less than 3.



Coster water machines provide top quality water and a top quality compliment to any store. With over 30 years in the business, Coster machines have a proven track record of dependability and success in the marketplace.

Locations/Applications

- Supermarkets
- Health Food Stores
- C-Stores
- Water Stores
- Drug Stores

Specifications:

- Height: 74 inches
- Depth: 26 inches
- Width: 48 inches
- Dry Shipping Weight:
450 lbs. (Bulk Water Units)
585 lbs. (Pressure Pump Units)
- Operating pressure: 100-125 PSI Max
(Pressure Pump Units)
- Product Water Dispensing Pressure: 5-40 PSI
- Plumbing connections: 1/2 inch FNPT (Feed)
1/2 inch FNPT (Drain)
- Electrical: 110 VAC 60HZ 15 A

A Division of Hiniker Company
58766 240th St. • Mankato, MN 56001
Telephone: 1-507-625-6621 • FAX: 1-507-625-9124
www.costereng.com



We reserve the right to amend these specifications at any time without notice. The only warranty applicable is the standard written Coster Engineering limited warranty. We make no other warranty, expressed or implied. Consult factory for details.